

**Technical Specifications**

<b>Power Supply</b>	9 ... 28VDC
<b>Power Consumption</b>	Standby: 0.2W, max. 0.9W at brightness 100%
<b>Loxone Tree Interface</b>	connection with Miniserver / Tree Extension
<b>Touch Area</b>	capacitive touch detection 12/14 touch points
<b>Click Feedback</b>	Yes
<b>Backlight</b>	Yes
<b>Temperature detection range</b>	-40 ... 125°C +/- 0.5°C -40 ... 257°F +/- 0.9°F

**Ambient Conditions**

<b>Temperature</b>	-20 ... 40°C / -4 ... 104°F
<b>Humidity</b>	max. 95% r.H. (non condensing)
<b>Ingress Protection</b>	IP44



For more information  
about this product, visit  
[loxone.com/help/touch-pure-flex-tree](https://loxone.com/help/touch-pure-flex-tree)

VI51024

**Loxone  
Electronics GmbH**  
Smart Home 1  
4154 Kollerschlag  
Austria

**Loxone UK**  
The Forum  
Station Road  
Theale, RG7 4RA  
United Kingdom



For additional information,  
declaration of conformity, visit  
[www.loxone.com/datasheets](https://www.loxone.com/datasheets)

# Touch Pure Flex Tree

Need Help?  
[loxone.com/support](https://loxone.com/support)



**Part No.: 100608 (White)**  
**Part No.: 100609 (Anthracite)**

## About the product

The Touch Pure Flex is your 100% personalized control device with up to 12 freely definable and positionable touch points. With the integrated LED matrix display, as well as 3 status LEDs, menus, values, texts and states can be displayed. The integrated lighting makes the Touch Pure Flex ideal for operation in low-light conditions or complete darkness.

## Safety Instructions

Installation must be carried out by a qualified electrician in accordance with the applicable regulations.

This device is free of maintenance and must only be cleaned with a dry cloth.

## Connecting Terminals

Terminal Type	DG220B
Wire Cross-Section	0.28 ... 0.8mm <sup>2</sup> / AWG23 ... 18
Stripping Length	5 ... 6mm / 0.2 ... 0.24"
Temperature Resistance	-40 ... 105°C / -40 ... 221°F

