



Product Service

Attestation of Conformity

No. E8A 082052 0338 Rev. 01

Holder of Certificate: **Shenzhen Keyu Power Supply Technology Co., Ltd.**

2~3F, No. 13, Lane3, Yuquan East Road
the 2nd Industrial park, Yulu
Guangming District
518000 Shenzhen
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Adaptors
(AC/DC ADAPTER)**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 657602114002

Date, 2022-05-10

(Laurent Yuan)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. E8A 082052 0338 Rev. 01

Model(s):

KA24D-xxxxxyyyzz, KA24D-xxxxxyyyzzH,
KA24D-xxxxxyyyDE
(xxx=090-360 stands for the rated output voltage
from 9.0VDC to 36.0VDC; yyyy=0100-2500 stands
for the rated output current from 0.10A to 2.50A;
zz=EU stands for the plug type, EU means
European plug.)

**Description of
Object:**

Rated Input: 100-240VAC, 50/60Hz, 0.65A Max

Rated Output: See below table for details

Protection Class: II

Model name	Rated output voltage (VDC)	Rated output current (A)	Max. rated output power (W)
KA24D-xxxxxyyyzz, KA24D-xxxxxyyyzzH, KA24D-xxxxxyyyDE	9.0-15.0	0.10-2.50	24.0
	15.1-24.0	0.10-1.50	24.0
	24.1-36.0	0.10-0.80	24.0

**Tested
according to:**

EN 55032:2015/A11:2020
EN 55035:2017/A11:2020
EN IEC 55014-1:2021
EN IEC 55014-2:2021
EN IEC 61000-3-2:2019/A1:2021
EN 61000-3-3:2013/A1:2019

Page 2 of 2

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 082052 0333 Rev. 01

Holder of Certificate: **Shenzhen Keyu Power Supply Technology Co., Ltd.**

2~3F, No. 13, Lane3, Yuquan East Road
the 2nd Industrial park, Yulv
Guangming District
518000 Shenzhen
PEOPLE'S REPUBLIC OF CHINA

Product: **Adaptors
(AC/DC ADAPTER)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 652102120402

Date, 2022-04-22

(Ricky Wang)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 082052 0333 Rev. 01

Model(s): KA24D-xxxxxyyyzz, KA24D-xxxxxyyyzzH,
KA24D-xxxxxyyyDE
(xxx=090-360 stands for the rated output voltage
from 9.0VDC to 36.0VDC; yyyy=0100-2500 stands
for the rated output current from 0.10A to 2.50A;
zz=EU stands for different the plug type, EU means
European plug.)

Parameters:

Rated Input: 100-240VAC, 50/60Hz, 0.65A Max

Rated Output: See below table for details

Protection Class: II

Degree of Protection: IP20

Model name	Rated output voltage (VDC)	Rated output current (A)	Max. rated output power (W)
KA24D-xxxxxyyyzz, KA24D-xxxxxyyyzzH, KA24D-xxxxxyyyDE	9.0-15.0	0.10-2.50	24.0
	15.1-24.0	0.10-1.50	24.0
	24.1-36.0	0.10-0.80	24.0

**Tested
according to:**

EN 62368-1:2014/A11:2017