

Insulation & Safety

Power Frequency Withstand Voltage	4000 V / 10 s, 1mA
Insulation Resistance	100 MΩ @ 500 VDC
Enclosure Flame Retardant Rating	UL 94-V0

Ambient Conditions

Temperature	-40 ... 70 °C / -40 ... 158 °F
Storage Temperature	-40 ... 85 °C / -40 ... 185 °F
Humidity	max. 85% r.H. (non-condensing)
Ingress Protection	IP40

Secondary Output Cable

Wire cross-section	1.5 mm ² / AWG 16
Cable length	2 m
Termination	tinned wire ends (5 ... 10 mm)

V120825

LOXONE

**Loxone
Electronics GmbH**
Smart Home 1
4154 Kollerschlag
Austria

Loxone UK
The Forum
Station Road
Theale, RG7 4RA
United Kingdom



For additional information,
declaration of conformity, visit
www.loxone.com/datasheets

5A Current Transformers 200A 24mm

Need Help?
loxone.com/support



Part No.: 100679

About the product


Set of three split-core current transformers designed for use with the Loxone Energy Meter for 1&5A Current Transformers Tree. With a 200 A primary rating and a 24 mm aperture, they are well suited for commercial applications and larger residential grid connections. Each CT includes a fixed 2 m color-coded cable, directional markings, and a cable tie mount for secure installation.

Features

- Set of 3 split-core CTs
- Primary current: 200 A / Secondary: 5 A
- Aperture: 24 mm
- Cable length: 2 m (fixed) with black and white leads
- Accuracy Class 0.5


Electrical Specifications

Rated Primary Current	200 A
Rated Secondary Current	5 A
Accuracy Class	0.5
Rated Load	1 VA
Operating Frequency	50/60 Hz
Linear Measurement Range	5 ... 120 % of rated primary current



Safety Instructions

Installation must be carried out by a qualified electrician in accordance with the applicable regulations. The device is free of maintenance and must only be cleaned with a dry cloth.

 Disconnect power before installing or removing the CT.