

Technical Specifications

Power supply	9 ... 28VDC
Power consumption	typ. 0.30W
Interfaces	Loxone Tree: 2 branches, up to 50 devices per branch max. 500m wire length per branch Loxone Link: connection with Miniserver
Power loss at max. load	0.12W
Ambient temperature	-40 ... 70°C / -40 ... 158°F
Humidity	max. 95% r. H. (non condensing)
Safety rating	IP20
Dimensions	88x35.4x57mm / 3.46x1.39x2.24" (LxWxH)
Maintenance & Cleaning	This device is free of maintenance and may only be cleaned with a dry cloth.

LOXONE

**Loxone
Electronics GmbH**
Smart Home 1
4154 Kollerschlag
Austria

Loxone UK
The Forum
Station Road
Theale, RG7 4RA
United Kingdom



For additional information,
declaration of conformity, visit
www.loxone.com/datasheets

V190924



Need Help?
loxone.com/support



LOXONE



Tree Extension

Part No: 100218

About the product

The Loxone Tree Extension enables interfacing with up to 100 Loxone Tree devices, 50 per branch. It can be used for a variety of nonsafety critical applications within your smart home.

Installation & electrical connection

The installation of this device has to be carried out by a qualified person. The device has to be fitted in accordance with building regulations for electrical and fire safety. If the device is not installed according to manufacturers guidelines the protection of the device may be affected.

Connection

Wire cross-section	0.25 ... 0.8mm ² / AWG23 ... 18
Stripping length	5mm / 0.2"
Temperature resistance	-40 ... 105°C / -40 ... 221°F

This folder is a part of the product!



For additional information,
visit www.loxone.com/help/tree

