Ambient Conditions

Temperature	-20 … 65 °C / -4 … 149 °F
Humidity	max. 95 % RH (non-condensing)
Ingress Protection	IP20

24 V DC & LOXONE Tree Terminals

Wire cross-section	0.25 … 1.5 mm² / AWG 28 … 16
Stripping length	7 mm / 0.28"
Temperature resistance	-40 … 100 °C / -40 … 212 °F

Safety & Installation Instructions

Installation must be carried out by a qualified electrician in accordance with applicable regulations.
This device is maintenance-free and must only be cleaned with a dry cloth.

For more information about this product, visit
loxone.com/help/curtain-control-tree

Loxone Electronics GmbH
Smart Home 1
4154 Kollerschlag
Austria

Loxone UK
The Forum
Station Road
Theale, RG7 4RA
United Kingdom

Loxone US
3060 Plaza Drive
Suite 105
Garnet Valley, PA 19060
United States

For additional information, declaration of conformity, visit
www.loxone.com/datasheets

Need Help?
loxone.com/support

V131126

Curtain Control Tree for Silent Gliss 5600

Part No.: 100993 (White)
Part No.: 100994 (Black)

LOXONE

About the product

The Curtain Control Tree brings Silent Gliss 5600 curtain systems into LOXONE Automatic Shading: open for daylight, closed against sun and for privacy — and still moved by a pull on the fabric. It sits in the drive's module slot, and the robust Tree interface integrates it directly.

Features

- Commissioning in minutes per drive
- Pull the curtain and the drive takes over — live in LOXONE
- Positioning from 0 to 100 % instead of open/close
- Fully automatic — manual control via app or touch at any time
- Supplied by the drive, whether it runs on AC or DC

Electrical Specifications

Supply Voltage	via Silent Gliss motor
Power Consumption	typ. 0.06 W, max. 0.07 W

Interface

LOXONE Tree	connection with Miniserver / Tree Extension



