LOXONE

Datasheet

Part No: 100613

About the product

Electrical Specifications

Supply voltage	9 ... 28 V DC
Power consumption	Standby: 0.2 W, max. 0.9 W at brightness 100 %

Interfaces

LOXONE Tree	Connection with Miniserver / Tree Extension

Operating Elements

Touch area	capacitive touch detection up to 12/14 touch points
Click feedback	Yes
Backlight	Yes

Measurement Range

Temperature	-10 ... 125 °C ± 0.5 °C / -14 ... 257 °F ± 0.9 °F
Humidity	0 ... 100 % RH ± 2 % (non-condensing)
CO2	400 ... 5 000 ppm (± 100 ppm, ± 10 % of reading)

Ambient Conditions

Temperature	-20 … 40 °C / -4 … 104 °F
Humidity	max. 95 % RH (non-condensing)
Ingress protection	IP20
CO2 sensor operating conditions	Temperature: 10 … 50 °C / 50 … 122 °F Humidity: 10 … 90 % RH (non-condensing) Max. dew point: 35 °C / 95 °F Pressure: 850 … 1100 hPa • Within the first 12 hours after power-up the CO2 sensor will automatically calibrate itself for the first time. During these period the sensor values may not be accurate. The CO2 sensor recalibrates itself over time, assuming exposure to fresh air (~400 ppm CO2) at least once per week.

Installation specifications


Recommended mounting height	135 cm / 53.15"


Connection Terminals

Terminal type	DG220B
Wire cross-section	0.28 … 0.8 mm² / AWG 23 … 18
Stripping length	5 … 6 mm / 0.2 … 0.24”
Temperature resistance	-40 … 105 °C / -40 … 221 °F

Connections

Connection Diagram






Product Characteristics

Colours	Anthracite: RAL 9005
Finish	Matte

Weight & Dimensions

Net weight	100 g
Total weight	142 g
Product dimensions	90 x 90 x 16 mm / 3.55 x 3.55 x 0.63” (L x W x H)
Product dimensions drawing	
Pack size	104 x 107 x 39 mm / 4.09 x 4.21 x 1.54” (L x W x H)

Certifications & Standards

Standards	• IEC 62368-1:2018 • UL 62368-1:2019 Ed. 3+R:22Oct2021 • CSA C22.2 No. 62368-1:2019 Ed. 3+U1 • SASO IEC 62368-1:2020
Certifications	

Installation must be carried out by a qualified electrician in accordance with the relevant regulations.

Published by

Loxone Electronics GmbH
Smart Home 1
4154 Kollerschlag
Austria
Tel: +43 7287 7070-0
loxone.com

Loxone UK Ltd.
The Forum
Station Road
Theale, RG7 4RA
United Kingdom

Loxone US Inc.
3060 Plaza Dr Suite 105
Garnet Valley, PA 19060
United States

Datenblatt

Part No: 100613

Über das Produkt

Elektrische Spezifikationen

Versorgungsspannung	9 ... 28 V DC
Leistungsaufnahme	Standby: 0,2 W, max. 0,9 W bei Helligkeit 100 %

Schnittstellen

LOXONE Tree	Verbindung mit Miniserver / Tree Extension

Bedienelemente

Tastbereich	kapazitive Berührungserkennung bis zu 12/14 Tastpunkte
Klick Feedback	Ja
Hintergrundbeleuchtung	Ja

Messbereich

Temperatur	-10 ... 125 °C ± 0,5 °C / -14 ... 257 °F ± 0,9 °F
Luftfeuchtigkeit	0 ... 100 % r. F. ± 2 % (nicht kondensierend)
CO2	400 ... 5 000 ppm (± 100 ppm, ± 10 % des Messwerts)

Umgebungsbedingungen

Temperatur	-20 … 40 °C / -4 … 104 °F
Luftfeuchtigkeit	max. 95 % r. F. (nicht kondensierend)
Schutzart	IP20
Betriebsbedingungen des CO2- Sensors	Temperatur: 10 … 50 °C / 50 … 122 °F Luftfeuchtigkeit: 10 … 90 % r. F. (nicht kondensierend) Max. Taupunkt: 35 °C / 95 °F Luftdruck: 850 … 1100 hPa • Innerhalb der ersten 12 Stunden nach dem Einschalten kalibriert sich der CO2-Sensor zum ersten Mal automatisch. Während dieser Zeit können die Sensorwerte ungenau sein. Der CO2-Sensor kalibriert sich im Laufe der Zeit selbst, vorausgesetzt, er wird mindestens einmal pro Woche frischer Luft (~400 ppm CO2) ausgesetzt.

Installationsspezifikationen


Empfohlene Montagehöhe	135 cm / 53,15"


Anschlussklemmen

Klemmentyp	DG220B
Leiterquerschnitt	0,28 … 0,8 mm² / AWG 23 … 18
Abisolierlänge	5 … 6 mm / 0,2 … 0,24”
Temperaturbeständigkeit	-40 … 105 °C / -40 … 221 °F

Anschlüsse

Anschlussplan






Produkteigenschaften

Farbe	Anthrazit: RAL 9005
Glanzgrad	Matt

Gewicht & Abmessungen

Nettogewicht	100 g
Bruttogewicht	142 g
Produktmaße	90 x 90 x 16 mm / 3,55 x 3,55 x 0,63” (L x B x H)
Produktmaßzeichnung	
Packmaß	104 x 107 x 39 mm / 4,09 x 4,21 x 1,54” (L x B x H)

Zertifizierungen & Standards

Normen	• IEC 62368-1:2018 • UL 62368-1:2019 Ed. 3+R:22Oct2021 • CSA C22.2 Nr. 62368-1:2019 Ed. 3+U1 • SASO IEC 62368-1:2020
Zertifizierungen	

Die Installation muss von einer qualifizierten Elektrofachkraft gemäß den einschlägigen Vorschriften durchgeführt werden.

Veröffentlicht von

Loxone Electronics GmbH
Smart Home 1
4154 Kollerschlag
Austria
Tel: +43 7287 7070-0
loxone.com

Loxone UK Ltd.
The Forum
Station Road
Theale, RG7 4RA
United Kingdom

Loxone US Inc.
3060 Plaza Dr Suite 105
Garnet Valley, PA 19060
United States